

**Superior<sup>®</sup>**  
**Uniform Exchange Series**  
**Bulk Hanging Garment Lockers**  
**(Full and Half Height)**

**General:** Lockers shall be "**Uniform Exchange Series, Bulk Hanging Garment Lockers**" as manufactured by List Industries Inc. or approved equal. Fabricate lockers square, rigid and without warp, with metal faces flat and free from dents or distortion. Make all exposed metal edges safe to touch. Weld frame members together to form rigid, one-piece structure. Weld, bolt, or rivet other joints and connections as standard with manufacturer. Grind exposed welds flush. Do not expose bolts or rivet heads on fronts of locker doors or frames except for fastening of number plates.

Lockers shall be **GREENGUARD Children & Schools Certified<sup>SM</sup>**

**Finishing:** All locker parts to be cleaned and coated after fabrication with a seven stage zinc/iron phosphate solution to inhibit corrosion, followed by a coat of high grade custom blend powder electrostatically sprayed and baked at 350 degrees Fahrenheit for a minimum of 20 minutes to provide a tough durable finish. Color: Gray

**Frame:** Fabricate of 16 gauge (minimum) channels, with integral continuous door stop/strike formed on both latch and hinge side vertical members.

**Access Door:** Door to be fabricated from single sheet prime 16 gauge with single bends at top, bottom and double-bends at the sides. Patron doors shall be plain (non-ventilated).

**Latch Assembly:** The latching mechanism for the access door shall be a multi-point latching system. Locking devise shall be designed for use with a padlock. Latch hooks shall be securely welded to the vertical frame channel on the strike side to engage the lock bar.

**Door Hinges:** Shall be a continuous piano hinge securely welded to the door and riveted to the frame.

**Body:** Fabricate back, dividers and sides of 24 gauge (minimum) sheet steel, with double flanged connections extending full height. Back to be ventilated with a ½" diameter hole pattern. Top, bottom and intermediate tier dividers shall be of 21 gauge (minimum) sheet steel with single return bends at all sides.

**Equipment:** Full Height: coat rod at top of compartment  
Half Height: coat rod at top of upper and lower compartment.

**Locks:** Prepared for padlock (by others).

**One-Year Warranty:** Superior Uniform Exchange lockers are covered against all defects in materials and workmanship excluding finish, damage resulting from deliberate destruction and vandalism under this section **for a period of one year.**